




Nokia 6102i Keyboard Replacement

Written By: Jonathan Brophy



INTRODUCTION

Removing the keyboard from the Nokia 6102i



TOOLS:

- [iFixit Opening Tools](#) (1)
 - [T6 Torx Screwdriver](#) (1)
-

Step 1 — Battery




- Press and hold the button at the bottom of the back side of the phone while sliding the back plate down to remove the back cover.
- Note: Images on the right side may be hovered over to reveal larger versions.

Step 2



- Lift up the battery from the inside of the phone.
- ⓘ Make sure to lift up from the bottom of the battery as shown.

Step 3 — Logic Board





- Using a .208 head [T-6 Screwdriver](#) remove the two screws at the bottom of the battery cavity.

Step 4



- Use a plastic opening tool to remove the silver cover over the antenna.
- ⓘ The covering may not pop right off. It may require some prying in different locations around the top covering.

Step 5





- Remove the two newly revealed .208 inch screws at the top using a T-6 screwdriver.

Step 6



- **WARNING:** Use extreme caution when removing and handling the logic board as it is very fragile.
- With caution, use a plastic pryor to separate the back silver casing from the front of the phone. This may require force.
- Disconnect the logic board from the small orange chip.

Step 7 — Keyboard



- Pop out the keyboard from the frame.
- ⓘ Once the logic board is removed, the keypad can be easily popped out from the frame with very little force.
- The picture is showing the three layers: the frame, the keyboard, and the logic board.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-21 03:44:05 AM.